

# AWH-10

## INK RIBBON



### Description

- Applicable to a wide range of receiving materials (plain paper, coated paper, synthetic paper, PET film, etc./more than 200s BEKK).
- Unique coating on the back allows reliable and superior matching qualities with the thermal head.
- Heat resistant

### Physical data

#### TTR properties

Grade	Wax - Resin			
Base material	Polyester film			
Base caliper	4.5	0.4, 5.5	0.5, 5.7	0.5µm
Ink color	Black			
Transmission density	More than 1.0			

#### Printing properties

Image density	More than 1.4 (on coated paper) *1
Receiving material	Plain paper, coated paper, synthetic paper, film (PET, PVC), etc. (which has more than 200s BEKK)

#### Durability of printed image

Resistance to smear and heat (50°C)	Decodability ANSI more than C
Resistance to penscanner	Decode rate : more than 90%
Resistance to light	Decodability ANSI more than A
Resistance to water	Decodability ANSI more than A

### Conditions

Usage condition	:	5 ≈ 35°C, 30 ≈ 80% RH
Storage condition	:	5 ≈ 35°C, 30 ≈ 85%RH
Storage life	:	48 months after manufacturing date

### Certificaties

Directive RoHS / Directive WEEE / Directive 2003/11/EC / Directive 2000/53/EC / Directive 76/769/EC

#### Disclaimer

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.